

# Hellerman Tyton SE28 Diesel Resistant Heatshrink



**Brand:** Competition Systems

**Product Code:** SE28

**Availability:** 7 Days

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

**Price: \$0.00**

## Short Description

SE28 is used for long-term protection of cables and wire harnesses in military equipment, motor sports and aviation.

## Description

### Features

- Flexible, high performance elastomeric heat shrink tubing
- Used in aerospace, defence, railway and automotive applications
- Resistant to diesel fuel, aviation and hydrolic fluids
- Provides a reliable protection against abrasion and mechanical damage
- Very suitable for protecting cables and wire harnesses

## Specifications

|  |  |
|--|--|
| Application Tool                                 | <a href="#">H5002, H5004, E4500</a>        |
| Colour   | Black (BK)                                 |
| Description Short (BMEcat) (max. 150 characters) | Heat Shrinkable Tubing 2:1 VG-Norm 3,2/1,6 |
| GLOBAL PART DESCRIPTION                          | SE28 3.2/1.6-POA-BK                        |
| Marking Text                                     | as per VG                                  |
| Pack Cont.                                       | 150m                                       |
| Package Quantity per                             | reel                                       |
| Printable (Yes/No)                               | No   |
| Product Family                                   | SE28                                       |
| Product Group                                    | Heat Shrinkable Tubing 2:1 - Elastomer     |
| Short Description                                | Diesel resistant shrink tubing             |
| Shrink Ratio                                     | 2:1  |
| Variant  | Standard-Wall                              |
| With inner glue (Yes/No)                         | No   |

## Material Specifications

|                                     |            |
|-------------------------------------|------------|
| Longitudinal Change After Shrinkage | -10 % max. |
| Recov. ? d max.                     | 1.6mm      |
| Recov. ? d max.                     | .06"       |
| Supplied ? D min.                   | 3.2mm      |
| Supplied ? D min.                   | .13"       |
| Wall (WT)                           | 0.8mm      |
| Wall (WT)                           | .03"       |

## Material and Specifications

|                               |                      |
|-------------------------------|----------------------|
| Designation as per VG-Norm    | VG 95343 T05 D 001 A |
| Dielectric Strength           | 24,5 kV/mm           |
| ELV compliant (Article 4 - 2) | YES                  |
| Flammability                  | self-extinguishing   |
| Halogenfree                   | No                   |

|                              |   |
|------------------------------|---|
| Hazardous good               | No  |
| Material                     | Elastomer, cross-linked (POA)                             |
| Min. Shrink Temperature - °C | +170 °C   |
| Operating Temperature - °C   | -75 °C to +150 °C   |
| Specifications               | NF F 00-608, SAE - AMS - DTL-23053,<br>VG 95343-5:2006-06 |
| Tensile Strength             | 12MPa   |